

CSci 5271
Introduction to Computer Security
Day 5: Low-level defenses and counterattacks

Stephen McCamant
University of Minnesota, Computer Science & Engineering


Outline

- Return address protections
- Announcements intermission
- ASLR and counterattacks
- W⊕X (DEP)

Canary in the coal mine



Adjacent canary idea



Terminator canary

- Value hard to reproduce because it would tell the copy to stop
- StackGuard: 0x00 0D 0A FF
 - 0: String functions
 - newline: fgets(), etc.
 - 1: getc()
 - carriage return: similar to newline?
- Doesn't stop: memcpy, custom loops

Random canary

- Can't reproduce because attacker can't guess
- For efficiency, usually one per execution
- Ineffective if disclosed

XOR canary

- Want to protect against non-sequential overwrites
- XOR return address with value c at entry
- XOR again with c before return
- Standard choice for c : see random canary

Further refinements

- More flexible to do earlier in compiler
- Rearrange buffers after other variables
 - Reduce chance of non-control overwrite
- Skip canaries for functions with only small variables
 - Who has an overflow bug in an 8-byte array?

What's usually not protected?

- Backwards overflows
- Function pointers
- Adjacent structure fields
- Adjacent static data objects

Where to keep canary value

- Fast to access
- Buggy code/attacker can't read or write
- Linux/x86: `%gs:0x14`

Complex anti-canary attack

- Canary not updated on `fork` in server
- Attacker controls number of bytes overwritten

Complex anti-canary attack

- Canary not updated on `fork` in server
- Attacker controls number of bytes overwritten
- ANRY BNRY CNRY DNRY ENRY FNRY
- search 2^{32} → search $4 \cdot 2^8$

Shadow return stack

- Suppose you have a safe place to store the canary
- Why not just store the return address there?
- Needs to be a separate stack
- Ultimate return address protection

Outline

Return address protections
Announcements intermission
ASLR and counterattacks
W⊕X (DEP)

Note to early readers

- This is the section of the slides most likely to change in the final version
- If class has already happened, make sure you have the latest slides for announcements

Outline

Return address protections
Announcements intermission
ASLR and counterattacks
W⊕X (DEP)

Basic idea

- "Address Space Layout Randomization"
- Move memory areas around randomly so attackers can't predict addresses
- Keep internal structure unchanged
 - E.g., whole stack moves together

Code and data locations

- Execution of code depends on memory location
- E.g., on 32-bit x86:
 - Direct jumps are relative
 - Function pointers are absolute
 - Data must be absolute

Relocation (Windows)

- Extension of technique already used in compilation
- Keep table of absolute addresses, instructions on how to update
- Disadvantage: code modifications take time on load, prevent sharing

PIC/PIE (GNU/Linux)

- "Position-Independent Code / Executable"
- Keep code unchanged, use register to point to data area
- Disadvantage: code complexity, register pressure hurt performance

What's not covered

- Main executable (Linux 32-bit PIC)
- Incompatible DLLs (Windows)
- Relative locations within a module/area

Entropy limitations

- Intuitively, *entropy* measures amount of randomness, in bits
- Random 32-bit int: 32 bits of entropy
- ASLR page aligned, so at most $32 - 12 = 20$ bits of entropy
- Other constraints further reduce possibilities

Leakage limitations

- If an attacker learns the randomized base address, can reconstruct other locations
- Any stack address → stack unprotected, etc.

GOT hijack (Müller)

- Main program fixed, libc randomized
- PLT in main program used to call libc
- Rewire PLT to call attacker's favorite libc functions
- E.g., turn `printf` into `system`


GOT hijack (Müller)

```
printf@plt:    jmp *0x8049678
...
system@plt:   jmp *0x804967c
...
0x8049678: <addr of printf in libc>
0x804967c: <addr of system in libc>
```

ret2pop (Müller)

- Take advantage of shellcode pointer already present on stack
- Rewrite intervening stack to treat the shellcode pointer like a return address
 - A long sequence of chained returns, one pop

ret2pop (Müller)



Outline

- Return address protections
- Announcements intermission
- ASLR and counterattacks
- $W \oplus X$ (DEP)

Basic idea

- Traditional shellcode must go in a memory area that is
 - writable, so the shellcode can be inserted
 - executable, so the shellcode can be executed
- But benign code usually does not need this combination
- $W \text{ xor } X$, really $\neg(W \wedge X)$

Non-writable code, $X \rightarrow \neg W$

- E.g., read-only .text section
- Has been standard for a while, especially on Unix
- Lets OS efficiently share code with multiple program instances

Non-executable data, $W \rightarrow \neg X$

- Prohibit execution of static data, stack, heap
- Not a problem for most programs
 - Incompatible with some GCC features no one uses
 - Non-executable stack opt-in on Linux, but now near-universal

Implementing $W \oplus X$

- Page protection implemented by CPU
 - Some architectures (e.g. SPARC) long supported $W \oplus X$
- x86 historically did not
 - One bit controls both read and execute
 - Partial stop-gap "code segment limit"
- Eventual obvious solution: add new bit
 - NX (AMD), XD (Intel), XN (ARM)

One important exception

- ▣ Remaining important use of self-modifying code: just-in-time (JIT) compilers
 - E.g., all modern JavaScript engines
- ▣ Allow code to re-enable execution per-block
 - `mprotect`, `VirtualProtect`
 - Now a favorite target of attackers

Counterattack: code reuse

- ▣ Attacker can't execute new code
- ▣ So, take advantage of instructions already in binary
- ▣ There are usually a lot of them
- ▣ And no need to obey original structure

Classic return-to-libc (1997)

- ▣ Overwrite stack with copies of:
 - Pointer to libc's `system` function
 - Pointer to `"/bin/sh"` string (also in libc)
- ▣ The `system` function is especially convenient
- ▣ Distinctive feature: return to entry point

Chained return-to-libc

- ▣ Shellcode often wants a sequence of actions, e.g.
 - Restore privileges
 - Allow execution of memory area
 - Overwrite system file, etc.
- ▣ Can put multiple fake frames on the stack
 - Basic idea present in 1997, further refinements

Beyond return-to-libc

- ▣ Can we do more? Oh, yes.
- ▣ Classic academic approach: what's the most we could ask for?
- ▣ Here: "Turing completeness"
- ▣ How to do it: reading for Thursday

Next slides

- ▣ Return-oriented programming (ROP)
 - And counter-defenses
- ▣ Control-flow integrity (CFI)